

Product Name	Model	Product Picture	Detail
Magnetic Lock	ZCEL-280D		<ul style="list-style-type: none"> - Magnet Lock for single door - Standard Bearing: 280kg/600LBS - Current: DC12V/450mA or DC24V/200mA - Dimension:L250*W47*H26mm - Weight: 2.0kg- Anti-residual magnetism designed - Suit for : wood door; glass door and metal Door
ZL bracket for ZCEL-280D	ZCEL-280ZL		<ul style="list-style-type: none"> - ZL bracket for ZCEL-280D series EM lock - Dimension: 250*50*30mm - Weight: 0.65kg - High Strength Aluminum material
U bracket for ZCEL-280D	ZCEL-280U		<ul style="list-style-type: none"> - U bracket for EL280 ZCEL-280D EM lock - Dimension: 180*43*28mm - Weight: 0.45kg - High Strength Aluminum material
Magnetic Bolt Lock	ZCBL-36		<ul style="list-style-type: none"> - Voltage: DC12V; Working Current: 120mA - Signal Output; low temperature; 0-6 seconds delay time - Dimension:L200*W34*H42mm - Weight: 0.8kg - Suit for : glass door
U bracket for ZCBL-36	ZCB-200G		<ul style="list-style-type: none"> - Material: Stainless Steel - Suitable for glass door - Size: 280*57*45mm - Including 1 pair 2 sets
Exit Button	ZCEX-S28		<ul style="list-style-type: none"> - NO/COM - Narrow Long Size Size: 91L*28W*20H(mm) - Weight: 0.065kg - Stainless Steel material
Breakglass	ZCEB-809G		<ul style="list-style-type: none"> - NO/NC/COM Breakglass Call Point - 3A@36V DC Max. - Fireproof PVC - Color : green
Remote	ZCR-807M		<ul style="list-style-type: none"> - Current: DC12V,8mA - Output NO/NC/COM - Frequency: 433MHz - Transmit Distance: 50m (in the open area) - Maximum Capable of 30 transmitters for 1 reciever
Power Supply	ZTA5AAACC		<ul style="list-style-type: none"> - input : AC110-260V - Output: DC12 V ,1% - Current output : 5A - Battery 12V5A